

# Echo


WALL LIGHT

Look no further than the Echo Wall Light for an impossibly thin beam of light for bathroom applications. This wall light has been refined to be as thin as possible across its arm to blend seamlessly into vanities. A unique protruding diffuser design delivers a wider distribution for task lighting applications.

- Ideal for vanity applications and for highlighting feature artwork in galleries and museums
- Excellent colour rendering with a CRI rating of 90+
- A slimline arm design for an unobtrusive wall addition
- Dot-free illumination set at a wide 110° beam angle for excellent task lighting

<b>600mm</b>
<b>Measurements (mm)</b>
<b>Absolute Luminous Flux</b>
12W (300mA)
660lm (at 3000K)
670lm (at 4000K)
<b>Beam</b>
110° (F)

<b>900mm</b>
<b>Measurements (mm)</b>
<b>Absolute Luminous Flux</b>
20W (500mA)
1165lm (at 3000K)
1175lm (at 4000K)
<b>Beam</b>
110° (F)



**Driver**  
**Power Factor** | >0.90  
 240V Built-in Non-Dimmable Driver  
**Dimming** | DALI Dim Optional (DALI driver must be remote)

**Notes**  
 Installation requires 30mm space above and below luminaire.

**Finishes**  
 UV Textured Black  
 UV Textured White

**General Specifications**  
**Material** | Powder Coated Aluminium, Frosted Acrylic Diffuser  
**IP** | 65  
**Warranty** | 3 Years



Top: Hotel wall application  
 Right: Protruded diffuser



<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>F</b>	<b>Product Family</b>	<b>Size</b>	<b>Finish</b>	<b>D</b>	<b>CCT</b>	<b>E</b>	<b>Beam</b>	<b>F</b>	<b>Driver</b>
ECHO	0600	TB	30	F	-	ECHO Echo Vanity Light	0600 0900	Textured Black Textured White	30	3000K 4000K	F	Flood	-	Standard Non-Dimmable Driver included
Example: <b>ECHO0600.TB30.F</b> Refer to data sheet for available configurations. Visit Product Toolbox at <a href="https://unios.com/echo">unios.com/echo</a> to configure compatible Osram/Tridonic DALI drivers.														